



PRODUCT INFORMATION

PROMIX[®] 200FE

- APPLICATION:** A processing aid and internal lubricant for synthetic and natural rubbers. Especially effective in highly polar elastomers.
- COMPOSITION:** Complex mixture of medium to higher molecular weight fatty acid esters and hydrocarbon inert carrier.

TYPICAL CHARACTERISTICS

- APPEARANCE:** Light colored pastilles
- SOFTENING POINT:** Performance: 50 – 62 C
- SPECIFIC GRAVITY:** Approximately 1.2
- ASH CONTENT:** Approximately 19.5% - 22%
- WATER CONTENT:** Approximately 6%
- PHYSIOLOGICAL DATA:** Refer to Material Safety Data Sheet
- DISCOLORATION:** None
- STORAGE STABILITY:** Minimum of one year under normal conditions
- PACKAGING:** 25 kg. polyethylene bags
- RECOMMENDED USE:** 1 - 3 phr. Add with fillers or late in mix cycle.

ADVANTAGES

- Improves dispersion of fillers.
- Promotes faster mixing, shortens mix cycle.
- Improves extrusion or calendering.
- Reduces die swell.
- Improves mold flow and release.
- Reduces scorch.
- Prevents sticking to rotors and rolls.

Revised: February 7, 2001 / PROMIX.200FE
CAB/Customer Service Department